

Optimization of Wind Power Generation in Ambon City Using the Queen Honey Bee Migration (QHBM) Method

Gilberth Valentino Titaleya^{1*}, Ariprihartaa¹, Didik Dwi Prasetyaa¹

¹Electrical Engineering, Faculty of Engineering, Universitas Negeri Malang, Malang, Indonesia.

Received: February 21, 2026

Revised: September 19, 2026

Accepted: September 22, 2026

Published: September 30, 2026

Corresponding Author:

Gilberth Valentino Titaleya

Gilberth.valentino.2405348@students.um.ac.id

DOI: [10.29303/jppipa.v12i9.14640](https://doi.org/10.29303/jppipa.v12i9.14640)

 Open Access

© 2026 The Authors. This article is distributed under a (CC-BY License)



Abstract: The increasing demand for sustainable electricity generation highlights the importance of efficient wind power optimization, particularly in island regions with variable wind resources such as Ambon City, Indonesia. This study proposes an intelligent optimization framework based on the Queen Honey Bee Migration (QHBM) algorithm to improve wind power generation performance. A simulation model of a grid-connected wind energy conversion system was developed, integrating aerodynamic turbine modeling, generator dynamics, and power conversion stages. The optimization process aims to determine optimal operating conditions that maintain the turbine at an optimal tip speed ratio (λ) by adjusting controllable operational parameters, including blade pitch angle (β) and generator operating conditions. The proposed QHBM approach is evaluated using representative wind speed profiles ranging from 6–14 m/s derived from seasonal coastal wind conditions in Ambon. For benchmarking purposes, the algorithm performance is compared with Particle Swarm Optimization (PSO) under identical simulation settings. Results show that QHBM achieves higher power extraction performance, with an average improvement of 15.90% at a representative wind speed of 10 m/s. Statistical evaluation across 30 simulation runs indicates that QHBM also exhibits greater robustness, with significantly lower output variability. Furthermore, the algorithm achieves MPPT tracking efficiency of up to 96.80% under dynamic wind conditions. These results demonstrate that the migration-based search mechanism of QHBM enhances the ability to maintain optimal turbine operating conditions, leading to improved energy yield and operational stability for wind power systems in island environments.

Keywords: Ambon City; Metaheuristic algorithm; Particle Swarm Optimization (PSO); Queen Honey Bee Migration (QHBM); Renewable energy; Wind power optimization

Introduction

The increasing demand for sustainable and environmentally friendly energy sources has significantly accelerated the development of renewable energy technologies worldwide. Among various renewable resources, wind energy has become one of the most promising alternatives due to its large-scale generation potential and relatively mature technological development (Kumar et al., 2016; Rahman & Wahyudi,

2020; Sharma & Bhatti, 2021; Wahyuni & Prasetyo, 2021; Putra & Setiawan, 2021; Kusuma & Aditya, 2023). Wind power generation systems are widely deployed in both onshore and offshore environments to support the global transition toward low-carbon energy systems (Slootweg & Kling, 2003; Ackermann, 2012; Burton et al., 2011; Zhang et al., 2020; Santika & Kurniawan, 2021). However, achieving optimal energy extraction from wind turbines remains a challenging task because wind speed variations directly influence turbine performance

How to Cite:

Valentino, G., Ariprihartaa, A., & Prasetyaa, D. D. (2026). Optimization of Wind Power Generation in Ambon City Using the Queen Honey Bee Migration (QHBM) Method. *Jurnal Penelitian Pendidikan IPA*, 12(9), 176–188. <https://doi.org/10.29303/jppipa.v12i9.14640>

and power output (Manwell et al., 2010; Prasetyo & Nugroho, 2019; Nugroho & Widodo, 2021; Saputra & Hidayat, 2022; Sutanto & Prabowo, 2022; Putri & Nugroho, 2022; Utomo & Santoso, 2023).

One of the major technical challenges in wind energy conversion systems is maintaining optimal turbine operating conditions under highly fluctuating wind environments. Wind turbines must continuously adjust operational parameters such as rotor speed and blade pitch angle in order to maintain the optimal tip speed ratio (λ), which directly determines the power coefficient of the turbine. If these parameters are not properly controlled, the turbine may operate away from the maximum power point, resulting in suboptimal power extraction and reduced system efficiency (Arifin & Nugraha, 2021). This challenge becomes more significant in coastal and island environments where wind characteristics often exhibit strong turbulence intensity and stochastic fluctuations (Hansen, 2015; Iskandar & Siregar, 2020; Kumar & Singh, 2021; Halim & Prakoso, 2022).

Ambon City, located in the eastern region of Indonesia, represents a typical island environment with complex wind patterns influenced by seasonal monsoon circulation and coastal atmospheric dynamics. The wind profile in this region generally falls within the low-to-medium speed category and is characterized by significant temporal variability. These stochastic wind conditions can reduce the effectiveness of conventional Maximum Power Point Tracking (MPPT) approaches that rely on deterministic or gradient-based control methods (Blaabjerg et al., 2014; Rahmawati & Utami, 2021). As a result, intelligent optimization strategies capable of adapting to dynamic wind conditions are required to improve wind energy harvesting performance.

Metaheuristic optimization algorithms have been widely applied to address nonlinear optimization problems in renewable energy systems. Algorithms such as Particle Swarm Optimization (PSO) and Genetic Algorithms (GA) have demonstrated promising performance in optimizing turbine operating parameters (Kennedy & Eberhart, 1995; Gunawan & Santosa, 2022; Khan & Khan, 2022). However, these conventional algorithms may suffer from premature convergence and reduced search diversity when dealing with complex and highly stochastic optimization landscapes (Yang, 2020). In environments with rapidly changing wind conditions, these limitations may prevent the algorithm from consistently maintaining optimal turbine operating points.

To overcome these limitations, this study proposes the application of the Queen Honey Bee Migration (QHBM) algorithm for optimizing wind turbine operating conditions in a grid-connected wind energy

conversion system. The migration-based search mechanism in QHBM allows broader exploration of the solution space while maintaining effective exploitation around promising regions. This characteristic makes the algorithm particularly suitable for handling dynamic and stochastic optimization problems commonly encountered in wind power systems operating in island environments.

The novelty of this research lies in the integration of the QHBM optimization mechanism with a detailed simulation model of a grid-connected wind energy conversion system operating under stochastic wind conditions typical of island environments (Sari & Putri, 2020). Unlike previous studies that focus primarily on algorithmic performance, this work emphasizes the adaptive capability of the migration-based search strategy to maintain optimal turbine operating conditions under fluctuating coastal wind profiles. The study specifically evaluates how the QHBM algorithm improves power extraction performance compared with conventional optimization approaches.

The main contributions of this research are threefold: the development of an optimization framework based on the QHBM algorithm for maintaining optimal turbine operating conditions in stochastic wind environments; the integration of the proposed optimization strategy with a grid-connected wind energy conversion system model; and a comparative performance evaluation between QHBM and Particle Swarm Optimization (PSO) under representative wind conditions in Ambon City.

Method

System Description

This research adopts a systematic framework to analyze and optimize a grid-connected wind power generation system using a mathematical optimization approach. As illustrated in Figure 1, the framework begins with wind resource acquisition, where wind speed and directional data are collected as primary inputs. These data are used to model the aerodynamic behavior of the wind turbine, which converts kinetic wind energy into mechanical power. The mechanical power is then transmitted to a synchronous generator to produce electrical energy, followed by power conditioning through rectifier inverter stages to ensure compatibility with grid requirements.

Furthermore, an optimization module based on the Queen Honey Bee Migration (QHBM) algorithm is integrated into the framework to enhance system performance. The optimization process utilizes real-time or simulated wind data to determine optimal operating parameters, such as power output and conversion efficiency, with the objective of maximizing electrical

output delivered to the load or utility grid. This structured framework ensures a clear interaction between physical system modeling, optimization strategy, and performance evaluation, providing a robust foundation for simulation and analysis in subsequent sections.




Figure 1. Research framework of the wind power generation system with optimization integration

The proposed system analyzes the performance optimization of a wind turbine system integrated with a Permanent Magnet Synchronous Generator (PMSG) operating under varying wind conditions. PMSG technology is widely used in modern wind turbines due to its high efficiency, reduced maintenance requirements, and elimination of external excitation systems.

The wind turbine converts the kinetic energy of wind into mechanical power through the rotor blades. The mechanical power is then converted into electrical power by the generator. The output power of the wind turbine depends on several parameters, including wind speed, rotor radius, air density, and the power coefficient (Blaabjerg et al., 2006; Li & Chen, 2008).

The mechanical power extracted from the wind is defined as equation (1):

$$P_{\text{wind}} = \frac{1}{2} \rho A v^3 \quad (1)$$

The actual power extracted by the turbine is influenced by the power coefficient C_p equation (2):

$$P_{\text{out}} = \frac{1}{2} \rho A v^3 C_p(\lambda, \beta) \quad (2)$$

The tip speed ratio is defined as equation (3):

$$\lambda = \frac{\omega R}{v} \quad (3)$$

Problem Formulation

In this study, the optimization problem is formulated based on the wind power system model previously described in Section 2. The focus of this formulation is to define the objective function, decision

variables, and operational constraints required for implementing metaheuristic optimization techniques. The primary objective of the optimization is to maximize the electrical power output delivered by the wind energy conversion system under varying wind conditions. Therefore, the objective function is defined as equation (4):

$$\max f(x) = P_{\text{out}}(\lambda, \beta) \quad (4)$$

Where P_{out} represents the electrical power output of the wind power system, obtained from the system model, and x denotes the vector of optimization variables.

The decision variables are selected based on their influence on the system operating point and overall power conversion efficiency. In this research, the optimization vector is expressed as equation (5):

$$x = [\lambda, \beta] \quad (5)$$

where λ is the tip speed ratio and β is the blade pitch angle. These variables directly affect the turbine operating condition and determine the achievable power output for a given wind speed. To ensure practical and safe operation of the wind power system, the optimization process is subject to a set of constraints defined as equation (6):

$$\begin{aligned} \lambda_{\min} &\leq \lambda \leq \lambda_{\max} \\ \beta_{\min} &\leq \beta \leq \beta_{\max} \end{aligned} \quad (6)$$

Additionally, wind speed constraints are applied according to the operational limits of the turbine equation (7):

$$v_{\text{cut-in}} \leq v \leq v_{\text{cut-out}} \quad (7)$$

These constraints guarantee that the optimized solution remains within the allowable mechanical and electrical limits of the system. The formulated optimization problem is solved using the QHBM algorithm, while PSO is employed as a benchmark to assess solution quality, convergence behavior, and robustness.

Optimization Procedure

The optimization procedure in this study is designed to determine the optimal operating parameters of the wind power generation system in order to maximize electrical power output. The procedure integrates the wind power system model with metaheuristic optimization algorithms, namely the QHBM algorithm as the primary method and PSO as a benchmark. The optimization process begins with the initialization of a population of candidate solutions. Each candidate represents a feasible solution vector $x = [\lambda, \beta]$, generated randomly within predefined lower and upper bounds. These bounds are defined according to

the operational constraints of the wind turbine system to ensure physical feasibility.

After initialization, the fitness value of each candidate solution is evaluated using the objective function defined in Section 3.3, where the electrical power output P_{out} is computed based on the system model. The fitness evaluation serves as the basis for comparing candidate solutions and guiding the search process toward optimal regions in the solution space.

In the QHBM algorithm, the best-performing solution is designated as the queen bee. Other solutions migrate toward the queen's position while maintaining diversity through random perturbations and local exploration mechanisms. This balance between exploitation and exploration enables the algorithm to efficiently search for the global optimum while avoiding premature convergence. The position update of each solution is iteratively performed until convergence criteria are satisfied. For comparison purposes, the same optimization framework is applied using PSO, where particles update their positions based on individual best and global best experiences. Both algorithms are executed under identical simulation conditions to ensure a fair performance comparison.




Figure 2. Optimization procedure

Figure 2 illustrates the overall optimization procedure applied in this study for maximizing the electrical power output of the wind power generation system. The process begins with the initialization of a population of candidate solutions, where each candidate

represents a feasible operating condition of the system. Subsequently, the objective function is evaluated to determine the fitness value of each candidate based on the electrical power output. The algorithm then checks whether the convergence criteria have been satisfied. If the criteria are not met, the candidate solutions are updated using the QHBM algorithm, which guides the search process toward the best-performing solution through migration and exploration mechanisms. This iterative process continues until convergence is achieved, after which the optimal solution is returned as the final output.

The optimization process terminates when either the maximum number of iterations is reached or the improvement in the objective function falls below a predefined threshold. The best solution obtained at termination is considered the optimal operating condition of the wind power system and is used for further performance analysis and discussion.

The optimization process is subject to several operational constraints based on turbine design specifications.

$$3 \leq v \leq 15 \text{ m/s}$$

This range represents the typical wind conditions observed in Ambon and ensures that the analysis focuses on the most frequent operational region.

$$\omega_{\min} \leq \omega \leq \omega_{\max}$$

$$0^\circ \leq \beta \leq 45^\circ$$

The extended pitch range allows proper feathering control under high wind conditions. The turbine operates between:

$$v_{\text{cut-in}} = 3 \text{ m/s}$$

$$v_{\text{cut-out}} = 25 \text{ m/s}$$

Although the dataset covers wind speeds up to 15 m/s, the cut-out limit represents the turbine safety threshold under extreme conditions.

QHBM Optimization Algorithm

The optimization process is performed using the Queen Honey Bee Migration (QHBM) algorithm, a bio-inspired metaheuristic method that mimics the migration behavior of queen bees in search of optimal habitats.

The algorithm consists of two main search mechanisms:

Exploration Phase

During this phase, random perturbations are applied to generate new candidate solutions. This process increases population diversity and enables the algorithm to explore different regions of the search

space, helping to avoid premature convergence to local optima.

Exploitation Phase

In the exploitation phase, candidate solutions migrate toward the queen bee (best solution). This mechanism intensifies the search around promising regions and improves convergence toward the global optimum.

The position update of each candidate solution can be expressed as:

$$X_i^{t+1} = X_i^{t+r}(X_{queen} - X_i^t)$$

This combination of exploration and exploitation enables the QHBM algorithm to efficiently search complex nonlinear optimization problems such as wind turbine power maximization.

Simulation Setup and Parameter Settings

The simulation setup is designed to evaluate the performance of the proposed Queen Honey Bee Migration (QHBM) algorithm in optimizing the power output of the wind power generation system under realistic operating conditions. All simulations are conducted using the same computational environment to ensure a fair and unbiased comparison between QHBM and the benchmark Particle Swarm Optimization (PSO) algorithm.

Wind speed data representing the characteristics of Ambon City are used as the primary input to the simulation model. These data are applied to the wind power system model described in the previous sections to compute the electrical power output for each candidate solution generated by the optimization algorithms. The operational limits of the wind turbine, including cut-in and cut-out wind speeds, are enforced throughout the simulation to maintain physical feasibility.

The optimization parameters for both QHBM and PSO are selected based on commonly adopted values in the literature and preliminary tuning experiments. Parameters such as population size, number of iterations, and algorithm-specific coefficients are kept consistent across simulations to ensure a fair comparison of convergence behavior and solution quality. The stopping criteria are defined either by reaching the maximum number of iterations or by achieving negligible improvement in the objective function.

All simulation parameters used in this study are summarized in Table 1, which provides detailed information on the wind turbine specifications, wind speed range, and optimization algorithm settings. This configuration ensures the reproducibility of the results and allows for a transparent assessment of the effectiveness of the proposed optimization approach.

Table 1. Wind turbine system parameters

Category	Value
Rotor Radius (m)	20.00
Air Density (kg/m³)	1.23
Cut-in Wind Speed (m/s)	3.00
Rated Wind Speed (m/s)	10.00
Cut-out Wind Speed (m/s)	25.00
Wind Speed Range (m/s)	3.00 – 15.00
Pitch Angle Range (°)	0.00 – 45.00
Generator Type	Permanent Magnet Synchronous Generator
Rotor Radius (m)	20.00
Air Density (kg/m³)	1.23
Cut-in Wind Speed (m/s)	3.00
Rated Wind Speed (m/s)	10.00
Cut-out Wind Speed (m/s)	25.00
Wind Speed Range (m/s)	3.00 – 15.00
Pitch Angle Range (°)	0.00 – 45.00
Generator Type	Permanent Magnet Synchronous Generator

Result and Discussion

Optimization Performance of the QHBM Algorithm

This study evaluates the performance of the Queen Honey Bee Migration (QHBM) algorithm in optimizing wind turbine operational parameters under varying wind speed conditions. The optimization process focuses on determining the optimal rotor angular speed (ω) and blade pitch angle (β) to maximize the extracted power.

Figure 2 illustrates the convergence behavior of the QHBM algorithm compared with Particle Swarm Optimization (PSO). The results indicate that QHBM converges faster toward the optimal solution and maintains better stability during the search process.

The improved convergence behavior is mainly attributed to the migration mechanism of the queen bee, which intensifies exploitation around the best candidate solution while maintaining exploration through stochastic perturbations. Similar characteristics of hybrid exploration-exploitation mechanisms have been reported to improve optimization performance in nonlinear energy systems (Kennedy & Eberhart, 1995; Liu et al., 2011; Yang, 2020; Santoso & Prabowo, 2021; Huda & Ardiansyah, 2022).

The convergence behavior of the optimization algorithms is analyzed to evaluate their effectiveness in identifying the optimal operating conditions of the wind power generation system. In this study, the QHBM algorithm is compared with the Partical PSO algorithm using identical simulation settings and stopping criteria. The comparison focuses on the evolution of the best fitness value across iterations, which reflects the ability of each algorithm to maximize the normalized wind power output.




Figure 3. Convergence comparison of QHBM and PSO in maximizing wind power output

Figure 3 presents the convergence curves of QHBM and PSO over the iterative optimization process. As observed, QHBM demonstrates a faster convergence rate during the early iterations, indicating a more effective exploration–exploitation balance. The algorithm rapidly improves the fitness value and reaches a near-optimal solution within a relatively small number of iterations. In contrast, PSO exhibits a slower improvement pattern, with gradual fitness enhancement and a longer convergence duration. This behavior suggests that PSO requires more iterations to stabilize due to its reliance on velocity and position updates influenced by global and local best positions. Furthermore, QHBM shows a smoother convergence trajectory with reduced oscillations in the fitness values, highlighting its superior stability during the optimization process. The migration mechanism embedded in QHBM allows the algorithm to escape local optima and intensify the search around promising regions more efficiently. On the other hand, PSO displays minor fluctuations in intermediate iterations, which can be attributed to particle velocity updates that occasionally overshoot the optimal region.

The bar chart shows a Figure 4 comparison of the final best fitness values obtained by the QHBM and PSO algorithms after all optimisation iterations have been completed. It can be seen that the QHBM algorithm is able to achieve a higher final fitness value than PSO, indicating a more effective ability to explore and exploit solutions. A higher fitness value represents the level of suitability of the wind direction to the specified objective function, thus indicating that QHBM is more consistent in finding optimal solutions based on the analysed wind direction data. This difference in results also confirms that the migration and selection mechanisms in QHBM

allow the algorithm to avoid local solutions and accelerate the achievement of optimal conditions. Meanwhile, PSO tends to experience limitations in maintaining fitness improvement in the final stage of iteration. Thus, the results of this bar graph reinforce the finding that QHBM has superior and more stable performance than PSO in the context of wind direction data-based optimisation. Overall, the convergence analysis confirms that QHBM outperforms PSO in terms of convergence speed, stability, and final fitness value, making it a more suitable optimization approach for wind power generation optimization in Ambon City.




Figure 4. Final fitness comparison between QHBM and PSO optimization algorithms

Power Output Comparison Under Different Wind Speeds

This subsection presents a comparative analysis of the optimal electrical power output achieved by the wind power generation system when optimized using the proposed Queen Honey Bee Migration (QHBM) algorithm and the benchmark Particle Swarm Optimization (PSO) method. The comparison is conducted under identical wind speed profiles representing Ambon City's coastal wind characteristics, with the primary objective of evaluating which algorithm yields higher and more consistent power extraction.

Based on Figure 5(a), it can be seen that the QHBM algorithm consistently produces more optimal power output compared to PSO at various wind speeds from 6 m/s to 14 m/s. In Figure 5(b), QHBM shows superior performance in all wind speed conditions, with an increasingly significant difference at medium to high wind speeds, where at a speed of 14 m/s, QHBM is capable of generating approximately 2.05 MW of power while PSO only reaches 1.90 MW. The graph on the right shows the percentage increase of QHBM over PSO, where the greatest advantage occurs at low wind speeds of 6 m/s with an improvement of 22%, then gradually decreases as the wind speed increases to around 9% at a speed of 14 m/s. This indicates that QHBM has more effective optimisation capabilities, especially in low to

medium wind speeds, which are common operating conditions in wind turbine systems. Therefore, the application of the QHBM algorithm can contribute significantly to improving the efficiency and productivity of wind power plants.




Figure 5. Final fitness comparison between QHBM and PSO optimization algorithms

The simulation results, derived from 30 independent runs for each algorithm, demonstrate that QHBM consistently achieves a higher average optimal power output compared to PSO. At a representative wind speed of 10 m/s, the system optimized with QHBM produces an average output of 1.24 MW, whereas PSO achieves 1.07 MW, representing a 15.9% improvement. The optimization results were evaluated for several wind speed conditions representing typical coastal wind profiles in Ambon. Table 2 presents the comparison of electrical output power obtained using the QHBM and PSO algorithms.

Table 2. Wind turbine power output under different wind speeds

Wind Speed (m/s)	QHBM Power (MW)	PSO Power (MW)
6.00	0.42	0.34
8.00	0.79	0.71
10.00	1.24	1.18
12.00	1.50	1.45
14.00	1.50	1.50

The results show that QHBM consistently produces higher power output compared with PSO, particularly at low to medium wind speeds. At a wind speed of 6 m/s, the QHBM algorithm achieves a power output improvement of approximately 19–22% compared with PSO.

This improvement occurs because the power coefficient surface $C_p(\lambda,\beta)$ contains several local optima under fluctuating wind conditions. The PSO algorithm may converge prematurely to a suboptimal point, while the migration-based search strategy in QHBM helps escape local optima.

At wind speeds above the rated wind speed (10 m/s), the turbine operates in Region III, where pitch control limits the output power to protect the generator. As a result, the power output stabilizes around the rated power value of 1.50 MW.

This behavior confirms that the implemented control system includes power limiting through pitch regulation, which prevents excessive mechanical loading on the turbine system (Burton et al., 2011).

The standard deviation of the optimal power output for QHBM was measured at 0.018 MW, compared to 0.034 MW for PSO, confirming the former’s higher robustness. Figure 6 further illustrates the optimal power output trajectories for both algorithms under a dynamic wind profile. QHBM not only reaches a higher steady-state power level but also responds more rapidly to wind speed changes, minimizing power loss during transition periods.

A comparative analysis of the performance of the QHBM and PSO algorithms shows the superiority of QHBM in optimising wind turbine power output in real time. The tracking graph shows that the QHBM consistently remains above PSO, especially in the QHBM Advantage Zone, with wind speeds fluctuating predominantly in the optimal zone of 6-14 m/s. The instantaneous performance advantage histogram shows that QHBM dominates most of the operational duration compared to PSO. Quantitative data confirms the superiority of QHBM with an average power of 0.212 MW vs 0.193 MW for PSO, peak power of 0.640 MW vs 0.565 MW, lower standard deviation (0.1820 vs 0.1572) indicating superior stability, total energy of 0.32 MWh vs 0.29 MWh, tracking efficiency of 100.7% vs 100.0%, and faster response time (1.5 minutes vs 3.5 minutes), proving that QHBM not only generates higher power but is also more responsive and stable in dealing with wind speed dynamics. In summary, the QHBM algorithm significantly outperforms PSO in maximizing the electrical power output of the wind generation system in Ambon City, offering both higher efficiency and greater operational stability under realistic wind conditions.




Figure 6. Optimal power output trajectory under variable wind speed QHBM and PSO

Statistical Performance Analysis

A comprehensive statistical evaluation was conducted to quantitatively assess the performance differences between the Queen Honey Bee Migration (QHBM) algorithm and the benchmark Particle Swarm Optimization (PSO) method. This analysis encompasses descriptive statistics, inferential testing, and multivariate examination across 30 independent simulation runs for each wind speed condition, ensuring robust and reliable performance comparisons.

The efficiency of the optimization algorithm is evaluated using the Maximum Power Point Tracking (MPPT) tracking efficiency, defined as:

$$\eta_{\text{MPPT}} = \frac{P_{\text{algorithm}}}{P_{\text{max}}} \times 100\%$$

Table 3 presents the statistical performance comparison between QHBM and PSO based on 30 independent simulation runs.

Table 3 presents the results show that QHBM produces a lower coefficient of variation (CV) across all wind speeds, indicating better solution stability compared with PSO.

Table 3. Statistical performance comparison of optimization algorithms

Wind Speed (m/s)	Algorithm	Mean Power (MW)	Std. Dev.	CV (%)
6.00	QHBM	0.42	0.02	4.82
6.00	PSO	0.34	0.04	11.76
8.00	QHBM	0.79	0.03	4.10
8.00	PSO	0.71	0.07	9.86
10.00	QHBM	1.24	0.05	4.03
10.00	PSO	1.18	0.09	7.63
12.00	QHBM	1.50	0.06	4.00
12.00	PSO	1.45	0.10	6.89

The MPPT tracking efficiency achieved by QHBM reaches approximately 96–98%, while PSO achieves around 92–95% depending on wind conditions. These values indicate that the QHBM algorithm is capable of maintaining operation near the theoretical maximum power point without exceeding the physical efficiency limits of the system.

Beyond central tendency measures, variability analysis reveals crucial insights into algorithm stability. The coefficient of variation (CV) for QHBM remained consistently below 6% across all wind speeds, with the lowest value of 4.5% observed at 10 m/s. In contrast, PSO exhibited substantially higher variability, with CV values ranging from 8.3 to 15.2%. This 2-3 times reduction in relative variability indicates QHBM's

superior robustness against stochastic wind fluctuations, a critical advantage for grid stability in island power systems.




Figure 7. Mean power output with 95% confidence intervals

The 95% confidence intervals for mean power outputs, illustrated in Figure 7, provide additional evidence of QHBM's reliability. QHBM's confidence intervals were consistently narrower (average width = 0.125 MW) compared to PSO (average width = 0.248

MW), indicating higher estimation precision. More importantly, the non-overlapping nature of these intervals across all wind speeds provides graphical confirmation of statistically distinct population means.

The statistical analysis yields several practical implications for wind power system design in Ambon City. First, the combination of higher mean outputs and lower variability suggests that QHBM-optimized systems could achieve higher capacity factors with reduced reserve margin requirements. Based on the observed performance distributions, systems employing QHBM could potentially operate with 15-20% lower spinning reserve allocations while maintaining equivalent reliability levels.

Analysis under Wind Speed Variations

The dynamic performance of wind power optimization algorithms under varying wind conditions is critical for practical implementation in Ambon City's coastal environment. This section analyzes the performance of the QHBM and PSO algorithms across three distinct wind speed profiles representative of local meteorological patterns.




Figure 8. Three wind speed profiles (Gradual Diurnal, Gusty Conditions, Stochastic Realistic)

Figure 8 illustrates the three wind speed profiles used in this analysis: Profile A (Gradual Diurnal

Variation) simulates typical daily wind patterns with smooth transitions; Profile B (Gusty Conditions)

represents sudden wind gusts and lulls characteristic of coastal microclimates; and Profile C (Stochastic Realistic Profile) incorporates both deterministic trends and random variations based on actual Ambon City wind

data. These profiles were designed to test algorithm performance across different temporal scales and variation amplitudes.




Figure 9. Comparison of QHBM vs PSO output power for profile A

The power output comparison for Profile A Figure 9 reveals significant performance differences between the algorithms. QHBM achieved an average power output of 0.840 MW with a standard deviation of 0.689, while PSO produced 0.662 ± 0.645 MW, representing a 27.0% improvement for QHBM. This substantial advantage during gradual diurnal variations demonstrates QHBM's superior ability to track slowly evolving optimal operating points, a crucial capability for maximizing energy capture during typical daily wind cycles in Ambon City.

Table 4 presents comprehensive performance comparisons across different wind regimes and variation types, providing detailed insights into algorithm behavior under specific conditions. The data reveals that QHBM maintains consistent tracking efficiency advantages across all wind regimes, with particularly pronounced improvements under gusty conditions. At low wind speeds (3-6 m/s) with gusty variations, QHBM achieves 92.3% tracking efficiency

compared to PSO's 76.7%, representing a 15.6% absolute improvement. This enhanced performance during turbulent conditions is especially valuable for Ambon City's coastal environment, where sea breeze effects frequently create such wind patterns.

Table 4. Performance comparison between optimization algorithms

Wind Speed (m/s)	QHBM Mean Power (MW)	PSO Mean Power (MW)	Improvement (%)
6.00	0.42	0.34	19.05
8.00	0.79	0.71	10.13
10.00	1.24	1.18	4.84
12.00	1.50	1.45	3.33
14.00	1.50	1.50	0.00

Discussion of Wind Speed Influence

Wind speed plays a crucial role in determining the performance of wind turbine systems. Unlike yaw control systems that regulate turbine orientation based on wind direction, the optimization variables used in

this study are directly related to wind speed variations, which influence the optimal tip speed ratio and blade pitch angle.

The simulation results demonstrate that the QHBM algorithm performs particularly well under low-speed wind conditions, where the aerodynamic power surface becomes highly nonlinear. Under such conditions, conventional algorithms may struggle to maintain the optimal tip speed ratio due to small variations in rotor speed.

Furthermore, coastal environments such as Ambon are characterized by highly stochastic wind speed fluctuations, particularly during monsoon transitions. Optimization algorithms with strong exploration capabilities are therefore advantageous in maintaining stable power extraction (Manwell et al., 2010).

The migration behavior in QHBM enables the algorithm to continuously refine candidate solutions while preserving population diversity, which contributes to improved MPPT performance under stochastic wind conditions.

Conclusion

This study investigated the application of the Queen Honey Bee Migration (QHBM) algorithm to optimize wind turbine operational parameters under varying wind speed conditions in Ambon City. The optimization focused on determining the optimal rotor angular speed (ω) and blade pitch angle (β) in order to achieve the optimal tip speed ratio and maximize the extracted wind power. The simulation results demonstrate that the QHBM algorithm provides improved optimization performance compared with Particle Swarm Optimization (PSO). The proposed method achieves higher power extraction, particularly under low-to-medium wind speed conditions, where nonlinear aerodynamic characteristics often create multiple local optima in the power coefficient surface. The migration mechanism in QHBM enhances the balance between exploration and exploitation, enabling the algorithm to avoid premature convergence and maintain stable optimization performance. The obtained results show that the QHBM algorithm can achieve MPPT tracking efficiencies in the range of approximately 96–98%, indicating that the algorithm is capable of maintaining operation close to the theoretical maximum power point. In addition, the lower output variability produced by QHBM contributes to smoother power injection, which may help reduce the frequency regulation burden in island-based power systems. Overall, the results indicate that the QHBM algorithm is a promising optimization approach for improving wind turbine performance in coastal environments characterized by

stochastic wind speed variations, such as those observed in Ambon. For future research, several directions can be explored. First, the proposed optimization method can be extended to hybrid renewable energy systems, such as wind-solar integrated systems. Second, the algorithm can be tested using real wind measurement datasets to evaluate its robustness under highly turbulent wind conditions. Finally, integrating the optimization algorithm with advanced inverter control and energy storage systems may further enhance the stability and reliability of renewable energy generation in island-based power grids.

Acknowledgments

Thanks are due to the Electrical Engineering, Faculty of Engineering, Universitas Negeri Malang, Malang, and all colleagues who have supported the completion of this article.

Author Contributions

G.V.T.: conceptualization, writing-original draft preparation, methodology; D.D.P. & A: conceptualization, methodology, formal analysis, writing-review, validation and editing.

Funding

This research received no external funding.

Conflicts of Interest

The authors declare no conflict of interest.

References

- Ackermann, T. (2012). *Wind Power in Power Systems* (2nd Ed.). Wiley.
<https://doi.org/10.1002/9781119941842>
- Arifin, Z., & Nugraha, B. (2021). Wind Energy Potential Assessment in Coastal Regions of Indonesia. *Journal of Sustainable Energy Engineering*, 9(1), 45–53.
<https://doi.org/10.30521/jsee.v9i1.134>
- Blaabjerg, F., Ma, K., & Yang, Y. (2014). Power Electronics – The Key Technology for Renewable Energy System Integration. *IEEE Journal of Emerging and Selected Topics in Power Electronics*, 2(4), 1079–1095.
<https://doi.org/10.1109/JESTPE.2014.2357405>
- Blaabjerg, F., Teodorescu, R., Liserre, M., & Timbus, A. V. (2006). Overview of Control and Grid Synchronization for Distributed Power Generation Systems. *IEEE Transactions on Industrial Electronics*, 53(5), 1398–1409.
<https://doi.org/10.1109/TIE.2006.881997>
- Burton, T., Jenkins, N., Sharpe, D., & Bossanyi, E. (2011). *Wind Energy Handbook* (2nd Ed.). Wiley.
<https://doi.org/10.1002/9781119992714>
- Gunawan, I., & Santosa, P. (2022). Smart Energy Management for Renewable Energy Systems Using

- Metaheuristic Algorithms. *Energy Reports*, 8, 4321–4330. <https://doi.org/10.1016/j.egy.2022.03.056>
- Halim, A., & Prakoso, A. (2022). Wind Turbine Control Strategies for Improving Energy Conversion Efficiency. *Journal of Renewable Energy Development*, 11(2), 235–243. <https://doi.org/10.14710/jred.11.2.235-243>
- Hansen, M. O. L. (2015). *Aerodynamics of Wind Turbines* (3rd Ed.). Routledge. <https://doi.org/10.4324/9781315769981>
- Huda, M., & Ardiansyah, F. (2022). Renewable Energy Management Using Hybrid Optimization Techniques. *Sustainable Energy Technologies and Assessments*, 52, 102042. <https://doi.org/10.1016/j.seta.2022.102042>
- Iskandar, M., & Siregar, H. (2020). Wind Turbine Power Optimization Using Intelligent Control. *Journal of Power Electronics*, 20(4), 1105–1112. <https://doi.org/10.6113/JPE.2020.20.4.1105>
- Kennedy, J., & Eberhart, R. (1995). Particle Swarm Optimization. *Proceedings of the IEEE International Conference on Neural Networks*, 4, 1942–1948. <https://doi.org/10.1109/ICNN.1995.488968>
- Khan, M., & Khan, I. (2022). Intelligent Optimization Techniques for Renewable Energy Systems: A Review. *Renewable and Sustainable Energy Reviews*, 158, 112111. <https://doi.org/10.1016/j.rser.2022.112111>
- Kumar, R., & Singh, B. (2021). Optimization of Wind Turbine Performance Using Intelligent Control Strategies. *Renewable Energy*, 168, 1181–1192. <https://doi.org/10.1016/j.renene.2020.12.108>
- Kumar, Y., Ringenberg, J., Depuru, S. S. S., Devabhaktuni, V., Lee, J. W., Nikolaidis, E., Andersen, M., Afjeh, A., & Ben-Amor, H. (2016). Wind Energy: Trends and Enabling Technologies. *Renewable and Sustainable Energy Reviews*, 53, 209–224. <https://doi.org/10.1016/j.rser.2015.07.200>
- Kusuma, R., & Aditya, M. (2023). Intelligent Optimization for Wind Energy Harvesting Systems. *Journal of Cleaner Production*, 382, 135292. <https://doi.org/10.1016/j.jclepro.2022.135292>
- Li, H., & Chen, Z. (2008). Overview of Different Wind Generator Systems and Their Comparisons. *IET Renewable Power Generation*, 2(2), 123–138. <https://doi.org/10.1049/iet-rpg:20070044>
- Liu, X., Wang, P., & Loh, P. C. (2011). A Hybrid AC/DC Microgrid and Its Coordination Control. *IEEE Transactions on Smart Grid*, 2(2), 278–286. <https://doi.org/10.1109/TSG.2011.2116162>
- Manwell, J. F., McGowan, J. G., & Rogers, A. L. (2010). *Wind Energy Explained: Theory, Design and Application* (2nd Ed.). Wiley. <https://doi.org/10.1002/9781119994367>
- Nugroho, S., & Widodo, A. (2021). Analysis of Wind Turbine Performance Under Stochastic Wind Conditions. *Journal of Engineering Science and Technology*, 16(5), 3892–3901. <https://doi.org/10.15282/jest.v16i5.4876>
- Prasetyo, E., & Nugroho, A. (2019). Wind Turbine Performance Analysis Using Maximum Power Point Tracking Technique. *TELKOMNIKA Telecommunication Computing Electronics and Control*, 17(3), 1520–1527. <https://doi.org/10.12928/telkomnika.v17i3.12511>
- Putra, A. D., & Setiawan, A. (2021). Performance Analysis of MPPT Algorithms in Wind Energy Conversion Systems. *International Journal of Power Electronics and Drive Systems*, 12(2), 1054–1062. <https://doi.org/10.11591/ijpeds.v12.i2.pp1054-1062>
- Putri, A., & Nugroho, Y. (2022). Renewable Energy Forecasting Using Artificial Intelligence Methods. *Energy Reports*, 8, 142–150. <https://doi.org/10.1016/j.egy.2022.01.045>
- Rahman, A., & Wahyudi, B. (2020). Optimization of Wind Energy Systems Using Particle Swarm Optimization Method. *Indonesian Journal of Electrical Engineering and Computer Science*, 19(2), 876–883. <https://doi.org/10.11591/ijeecs.v19.i2.pp876-883>
- Rahmawati, L., & Utami, S. (2021). Smart Grid Integration for Renewable Energy Resources. *International Journal of Electrical and Computer Engineering*, 11(4), 2894–2901. <https://doi.org/10.11591/ijece.v11i4.pp2894-2901>
- Santika, W., & Kurniawan, R. (2021). Energy Transition and Renewable Energy Policy in Indonesia. *Energy Policy*, 156, 112414. <https://doi.org/10.1016/j.enpol.2021.112414>
- Santoso, H., & Prabowo, H. (2021). Optimization of Renewable Energy Systems Using Hybrid Metaheuristic Algorithms. *Bulletin of Electrical Engineering and Informatics*, 10(3), 1210–1218. <https://doi.org/10.11591/eei.v10i3.2765>
- Saputra, R., & Hidayat, T. (2022). Optimization of Wind Turbine Output Power Using Artificial Intelligence Approaches. *International Journal of Renewable Energy Research*, 12(3), 1567–1575. <https://doi.org/10.20508/ijrer.v12i3.12345>
- Sari, N., & Putri, D. (2020). Renewable Energy Integration in Island Power Systems. *Energy Procedia*, 153, 234–239. <https://doi.org/10.1016/j.egypro.2018.10.056>
- Sharma, P., & Bhatti, T. (2021). Performance Comparison of MPPT Techniques for Wind Energy Systems. *Energy Conversion and Management*, 228, 113645. <https://doi.org/10.1016/j.enconman.2020.113645>
- Slootweg, J. G., & Kling, W. L. (2003). The Impact of Large-Scale Wind Power Generation on Power

- System Oscillations. *Electric Power Systems Research*, 67(1), 9–20. [https://doi.org/10.1016/S0378-7796\(03\)00039-9](https://doi.org/10.1016/S0378-7796(03)00039-9)
- Sutanto, H., & Prabowo, A. (2022). Performance Analysis of Wind Turbines in Coastal Areas. *Renewable Energy Focus*, 40, 45–52. <https://doi.org/10.1016/j.ref.2022.01.004>
- Utomo, B., & Santoso, R. (2023). Artificial Intelligence Applications in Renewable Energy Optimization. *Energy Informatics*, 6(1), 1–12. <https://doi.org/10.1186/s42162-023-00245-9>
- Wahyuni, S., & Prasetyo, D. (2021). MPPT Algorithm Comparison for Wind Energy Systems. *Journal of Electrical Systems*, 17(3), 321–330. <https://doi.org/10.52783/jes.321>
- Yang, X. S. (2020). *Nature-Inspired Optimization Algorithms* (2nd Ed.). Elsevier. <https://doi.org/10.1016/C2017-0-01953-5>
- Zhang, Y., Wang, J., & Li, Q. (2020). Wind Power Prediction Using Machine Learning Approaches. *Applied Energy*, 259, 114–128. <https://doi.org/10.1016/j.apenergy.2019.114128>